

S T I STEYR

**Multi Armament Weapon Station
on Armored Multi Mission Vehicle**



Armored Multi Mission Vehicle 4x4

Ballistic Protection Level up to

European Standard EN 1063 BR7 European Standard EN 1522 FB7 STANAG 4569 Level 2

Dimensions & Weight

Length	5380 mm
Width	2110 mm
Vehicle Height (roof line)	2055 mm
Vehicle Height with WS609M in Combat Position	2910 mm
Vehicle Height with folded WS609M in Transport Position	2545 mm
Wheelbase	2850 mm
Gross Vehicle Weight	6500 kg

Engine

V8 Diesel engine with exhaust Turbo charger and Intercooler- Common rail direct injection
Water cooled, capable to operate in high ambient temperatures and desert environment

max. engine Power: up to 221kW (300HP)
max. torque: up to 650Nm

Drivetrain

Gear-box: 6-speed fully automatic transmission
Transfer Case: 2-speed high-low range- with differential lock
Axles: Heavy Duty Coil Spring Suspension
100% locking differentials

Performance

Speed up to	130 km/h
Range up to	550 km
Acceleration 0 - 60 km/h	9.5 sec
Fuel Tank Capacity	140 l
Gradeability up to	80 %
Side Slope up to	45 %
Turning Radius	6.3 m

Technical Data WS 609M

Calibre 5.56 mm	600 rounds Ammo supply
Calibre 7.62 mm	350 rounds Ammo supply
Calibre 12.7 mm	160 rounds Ammo supply
Calibre 40 mm AGL	44 rounds Ammo supply
Traverse range	n x 360°
Elevation range	-10° to +45°

Special Features

Left or Right hand power steering
Tire Inflation System for highest Mobility
12 V / 24 V DC Electric System
Fitted For Radio

Various MMV Vehicle Configurations



High Roof Ambulance



Anti-Riot Police



Command & Control



Radar & Surveillance



Reconnaissance Forward Observer

STEYR Trucks

Sales and Services International GmbH

Hohe-Linde-Str. 1
4595 Waldneukirchen
Austria

Tel.: +43 7257 93001

Fax: +43 7257 93001 901

E-Mail: office@sti-steyr.com

<http://www.sti-steyr.com>

STI STEYR