

S T I STEYR

Armored Multi Mission Vehicle
for Homeland Security Missions



Armored Multi Mission Vehicle

Kinetic Energy Protection up to	Mine Blast Protection up to	IED Protection up to
CEN B7 / STANAG 4569 Level 2	STANAG 4569 Level 2a	20 kg TNT

Dimensions & Weights		Performance	
Length	5380 mm	Speed up to	130 km/h
Width	2110 mm	Range up to	550 km
Vehicle Height (roof line)	2055 mm	Acceleration 0 - 60 km/h	9.5 sec
Wheelbase	2850 mm	Turning Radius	6.3 m
Gross Vehicle Weight	6.500 kg	Gradeability up to	80 %
		Side Slope up to	45 %

Special Features

- Camera & Recording System
- Strobe Lights, Siren & Public Announcement System
- Tire Inflation System for highest Mobility
- Barricade Remover
- Various Weapon Stations: Internal Security Turret, Remote Control Weapon Stations, Roof Rings
- Wire Cutter
- Fitted For Radio 12V/24V
- Run Flat System
- Fire Suppression Systems
- Gun Ports

Internal Security MMV Vehicle Configurations

- Armored Personnel Carrier
- Armored Command & Control Vehicle
- Armored Ambulance
- Platoon Command Vehicle
- Fast Response Fire Fighting Vehicle
- Detection & Jamming Vehicle

Vehicle Engine	Euro 3 - Euro 6	Drivetrain
V8 Diesel engine with exhaust Turbo charger and Intercooler- Common rail direct injection Water cooled, capable to operate in high ambient temperatures and desert environment		Gearbox: 6-speed fully automatic transmission
Engine Power up to:	300 HP	Transfer Case: 2-speed high-low range with differential lock
max. Torque up to:	650 Nm	Axles: Heavy Duty Coil Spring Suspension with hydraulic shock absorbers & stabilizer bar 100% locking differentials
Protected Fuel Tank :	140 l	Steering: Left or Right hand power steering



STEYR Trucks

Sales and Services International GmbH

Hohe-Linde-Str. 1
4595 Waldneukirchen
Austria

Tel.: +43 7257 93001

Fax: +43 7257 93001 901

E-Mail: office@sti-steyr.com

<http://www.sti-steyr.com>

